

Other Accessories



Clips for detonating cord / Cordtexclip

Clips of yellow plastic for connecting detonating cords, Exel™ shock tubes, detonators, etc.

Supplied in cartons of 500 pcs.

Single Extension Wire

ELUB Ø0.61 mm, yellow PE insulation with a thickness of 0.60 mm, approved in accordance with Swedish Standard. Resistance 5.6 Ohm/100 m.

Supplied in rolls of 250 m.

Coupling Sleeves

Yellow and contains an aluminium tube filled with insulation mass. Coupling sleeves should be used in wet weather for insulating wire ends on electric detonators, extension wire and shot firing cable.

Supplied in boxes of 50 pcs.

Bore Hole Plugs

A bore hole plug reduces the risk of the bore hole being obstructed by stone and drill cuttings from the rock surface and is an efficient marker of the completed but uncharged holes.



Assortment

Size	Number per box	Diameter on drill hole plug mm	Diameter on the drill hole mm
1	360	30 - 45	30 - 40
2	250	38 - 58	40 - 50
3	100	50 - 80	50 - 75
4	176	60 - 132	75 - 120

Lid can be delivered for the drill hole plug size 4.

Shot Firing Cable

Approved shot firing cable – approval number SP SU 9402 is a high quality cable.

Assortment

Type	Square mm ²	Insulation thickness mm	Resistance per 100 m
REXV	2 x 1.50	0.9 + 1.2	2.5 Ohm

The shot firing cable is yellow and are in length of 100 m can be with or without stand.



Charging Rod

Charging rods are used for charging explosives into the drill holes. They are made from Norwegian pine trees.





Assortment

Charging Rods made of wood	
Diameter	Length
22 mm	Bundle of 100 m
25 mm	Bundle of 50 m
32 mm	Bundle of 50 m

Length can be ordered from 3,5 – 5,5m.

Disclaimer

© 2021 DEXPLOC A/S. All rights reserved. All information contained in this document is provided for informational purposes only and is subject to change without notice. Since DEXPLOC A/S cannot anticipate or control the conditions under which this information and its products may be used, each user should review the information in the specific context of the intended application. To the maximum extent permitted by law, DEXPLOC A/S specifically disclaims all warranties express or implied in law, including accuracy, non-infringement, and implied warranties of merchantability or fitness for a particular purpose. DEXPLOC A/S specifically disclaims, and will not be responsible for, any liability or damages resulting from the use or reliance upon the information in this document.

The word DEXPLOC with associated logo are trademarks of DEXPLOC A/S.