DEXPLOC TECHNICAL INFORMATION

Heavy Blasting Mat



Description

HEAVY BLASTING MAT constructed of steel reinforced tire threads of trucks, woven with galvanized steel wire Ø13 mm (144 threads, tensile strength min. 9.100 kp) and reinforced with lifting wire Ø16 mm and locked with 3 wire locks at each section. The mats are supplied rolled and can be ordered in different lengths and dimensions.



Assortment

Size	Type S-2/4	Type S-2/6	Type S-2/8	Туре S-2/10	Weight
(m)	Number of wire	Number of wire	Number of wire	Number of wire	ca. kg
2 x 3	4	-	-	-	450
3 x 2	-	6	8	10	450
3 x 3	-	6	8	10	675
3 x 4	-	6	8	10	900
3 x 5	-	6	8	10	1.125
3 x 6	-	6	8	10	1.350

Heavy Blasting Mats are produced on orders.

BLASTING MAT made of steel reinforced tires from passenger cars.



Assortment

Size (m)	Weight app. kg
0.8 x 1.4	40
0.8 x 1.8	60
1.7 x 1.5	80
1.7 x 2.0	110
1.7 x 3.0	165

Disclaimer

© 2021 DEXPLOC A/S. All rights reserved. All information contained in this document is provided for informational purposes only and is subject to change without notice. Since DEXPLOC A/S cannot anticipate or control the conditions under which this information and its products may be used, each user should review the information in the specific context of the intended application. To the maximum extent permitted by law, DEXPLOC A/S specifically disclaims all warranties express or implied in law, including accuracy, non-infringement, and implied warranties of merchantability or fitness for a particular purpose. DEXPLOC A/S specifically disclaims, and will not be responsible for, any liability or damages resulting from the use or reliance upon the information in this document.

The word DEXPLOC with associated logo are trademarks of DEXPLOC A/S.

DEXPLOC A/S Smedeland 7 | DK-2600 Glostrup | Denmark info@dexploc.com | www.dexploc.com | Telefon +45 43 45 15 38